

# A/C/C



## ABOUT THE PRODUCT

A/C technology's highest performance parallel shaft.

## SPECIFICATIONS

- High-strength carbon fiber bonded to a precision 7075 alloy core tube
- Polished carbon finish
- Guaranteed straightness:  $\pm .002''$
- Weight tolerance:  $\pm 0.5$  grains
- Components—sold separately

## FEATURED TECHNOLOGY

MADE IN  
USA

Size	Shaft Weight	Spine @28" Span	Stock Length	Point/Insert Sizes	Bushing	G Nock	Heavy Wt.	Med. Wt.	Light Wt.	Extra Light Wt.
	Grains per Inch	Deflection in Inches	Inches	Inches	Grains	Grains	Grains	Grains	Grains	Grains
2-00	4.7	1.500	28	-00	-	7	-	50	-	-
3L-00	5.1	1.300	28.5	-00	-	7	-	50	-	-
3-00	5.5	1.150	28.5	-00	-	7	-	-	-	50
2L-04	6.1	1.020	29	-04	2	7	100	80	70	60
2-04	6.5	0.920	29.5	-04	2	7	100	80	70	60

3X-04	6.7	0.830	29.5	-04	2	7	100	80	70	60
3L-04	7.0	0.750	30	-04	2	7	100	80	70	60
3-04	7.2	0.680	30	-04	2	7	100	80	70	60
3L-18	7.5	0.620	31	-18	3	7	-	100	82	70
3-18	7.8	0.560	31	-18	3	7	-	100	82	70
3-28	8.1	0.500	31.5	-28	4	7	-	100	87	70
3-39	8.6	0.440	31.5	-39	5	7	-	100	85	70
3-49	8.8	0.390	32	-49	6	7	-	-	100	80
3-60	9.5	0.340	32.5	-60	7	7	-	-	108	90
3-71	9.9	0.300	33	-71	8	7	-	-	114	90